


## FEATURES

- Low Forward Voltage
- High Surge Current Capability
- Low Leakage Current
- Low Inductance Package

## APPLICATIONS

- Field Supply For DC Motors
- Line Rectifiers For Transistorized AC Motor Controllers
- Non-controllable Rectifiers For AC/DC Converter



## MODULE TYPE

TYPE	Circuit Diagram		VRRM (Repetitive Peak Reverse Voltage)	VRSM (Non-Repetitive Peak Reverse Voltage)	Unit
	B	DK			
MMD130S120B	MMD130S120DK	1200	1300	V	
MMD130S140B	MMD130S140DK	1400	1500		
MMD130S160B	MMD130S160DK	1600	1700		
MMD130S180B	MMD130S180DK	1800	1900		

## ABSOLUTE MAXIMUM RATINGS

*T<sub>c</sub>=25°C unless otherwise specified*

Symbol	Parameter	Test Conditions	Values	Unit
I <sub>F(AV)</sub>	Average Forward Current	Single phase, half wave, 180°conduction, T <sub>c</sub> = 95°C	130	A
I <sub>F(RMS)</sub>	R.M.S. Forward Current		204	
I <sub>FSM</sub>	Non-Repetitive Surge Forward Current	1/2 cycle, 50HZ, peak value T <sub>c</sub> =45°C	3500	
		1/2 cycle, 60HZ, peak value T <sub>c</sub> =45°C	3800	
I <sup>2</sup> t	I <sup>2</sup> t (For Fusing)	1/2 cycle, 50HZ, peak value T <sub>c</sub> =45°C	61.2	KA <sup>2</sup> s
		1/2 cycle, 60HZ, peak value T <sub>c</sub> =45°C	60.0	KA <sup>2</sup> s
P <sub>D</sub>	Power Dissipation		625	W
T <sub>J</sub>	Junction Temperature		-40 to +150	°C
T <sub>STG</sub>	Storage Temperature Range		-40 to +125	°C
V <sub>ISO</sub>	Isolation Breakdown Voltage	AC, 50Hz(R.M.S), t=1minute	3000	V
Torque	Module-to-Sink	Recommended (M6)	3~5	N.m
Torque	Module Electrodes	Recommended (M6)	3~5	N.m
R <sub>th (J-C)</sub>	Junction-to-Case Thermal Resistance		0.2	K /W
Weight			170	g

# MMD130S

## ELECTRICAL AND THERMAL CHARACTERISTICS $T_C=25^\circ\text{C}$ unless otherwise specified

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$I_{RM}$	Max.Reverse Leakage Current	$V_R = V_{RRM}$			500	$\mu\text{A}$
		$V_R = V_{RRM}, T_J = 125^\circ\text{C}$			10	mA
$V_F$	Forward Voltage	$I_F = 400\text{A}$			1.5	V
$V_{T0}$	For power-loss calculations only				0.85	V
$r_T$	$T_J = 125^\circ\text{C}$				1.6	m $\Omega$




Figure1. Forward current vs.voltage drop




Figure2. Diode Power dissipation vs.  $I_{F(AV)}$




Figure3. Max Non-Repetitive Forward Surge Current




Figure4. Forward current vs. Case temperature





Figure5. Transient Thermal Impedance



Dimensions in Millimeters  
Figure6. Package Outline